



HAND ASCENDER

STANDARD : CONFORMING TO EN567:2013

INDUSTRY	IDEAL APPLICATIONS
Cement	Rope Access Ascending
Steel	
Aluminium	

SPECIAL FEATURES



MECHANICAL CHARACTERISTICS

Material - Aluminium alloy
Weight - 194 gm
Finish - Coloured, Anodized
Use with 10.5mm Kernmantle Rope

PHYSICAL PARAMETERS

Light weight Aluminium body
Toothed clamp to grip the rope
Rubber moulded handle to grip the device
Various connection points on the device to connect other rope access equipments

TEST COMPLIANCE - DYNAMIC STRENGTH

When subjected to a fall with a rigid mass of 100 kg., the braking force is less than 6 kN, and the arrest distance is less than 1.5 m

STORAGE

Store the retractable in a dry area away from ultraviolet rays

Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold.



FEATURES

Light weight corrosion resistant design provides durability
Easy to use and control the device with single hand using the clamp
Moulded grip on the handle is ergonomically designed allow easy and effortless grip
Various connection points on the device make it easy to use and complete the ascend

MARKINGS

Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacturing
Material
Approvals & EN
Instruction Pictogram

CLEANING

Use clean piece of cloth to wipe the dust

PACKING

1 piece per polybag