



TECHNICAL DATA SHEET

SN003 - SAFETY NET FOR FALL PROTECTION

Safety Net:

Safety Net is a Secondary Fall arrest measure to ensure workers safety and efficiency by providing a collective level of protection.

Features:

- Durable and resistant to harsh environments
- High-strength materials for maximum load capacity
- Customizable sizes and shapes to fit specific applications
- Easy installation and maintenance
- Manufactured with ISI Marked Rope & as per IS 11057:1984

Applications:



CONSTRUCTION SITE



MANUFACTURING FACILITIES




OIL AND GAS REFINERIES



WAREHOUSES AND LOGISTICS CENTERS



HEAVY INDUSTRIES (MINING, SHIPPING, ETC)



Weight: (Size: 10 x 5mtr)

12 KGS Approx

SN003 Safety Net (Double Layer)

Specifications:

Border Rope:	12 mm PP Rope (ISI Marked) Breaking Strength 2210kgf.
Mesh Rope:	4mm Dia PP Rope
Breaking Strength	214 Kg
Mesh Size:	100mm x 100mm
Fabrication Type:	Hand Knotted
2nd Layer	0.75mm Overlay HDP Net, having mesh size 20-25mm
Certifications	Manufacturer Test Certificate provided at the time of supply.
Tie Rope & Tie Cord:	12mm dia PP rope of 2 meter length at for 4 corner of border rope only. & Tie cord of 2 mtr at every 1.5 mtr interval.
Standard Size:	As per your requirement (Minimum Length & Width Should be 3 Mtr)
Standard / Approved:	Rope Certified to IS 5175: 1992, Safety Net as per IS:11057:1984
Marking/Lable	Manufacturer Name/Logo, Model No. , Batch No. , Size

Udyogi