






**PR 14**  
Polyamide Rope

STANDARD : CONFORMING TO EN 353-2:2002

INDUSTRY	IDEAL APPLICATIONS	SPECIAL FEATURES
Construction	Working at Height	 FALL ARREST  STRONG  TEMPORARY ANCHORAGE
Telecommunication		
Transmission	Fall Arrest	



MECHANICAL CHARACTERISTICS	
Rope Material - Polyamide Rope	Breaking Strength - 22 kN
Rope Dia - Ø 14 mm Rope	

FEATURES
Stitching Threads - High tenacity virgin multi-filament polyester
One side snap hook EASY 308 and other side end loop
Tie of anchor line made of polyamide twisted 3 strands rope

TEST COMPLIANCE - STATIC STRENGTH
Withstands a load of 22 kN for 3 minutes each attachment element

AVAILABLE LENGTH
10, 20, 30, 40, 50, 60,70, 100, 150 and 200 meter

MARKINGS
Manufacturers Logo, details & mailing address
Model No., Batch No., Serial No.
Year of Manufacturing
Material
Approvals & EN
Instruction Pictogram

STORAGE
Store in a dry area away from ultra violet rays
Do not store in direct / high heat or sunlight as this may distort the colour
Can be stored and transported in their original cartons to avoid corrosion due to atmospheric moisture, excessive heat or cold

CLEANING
Use clean piece of cloth to wipe the dust

PACKING
1 roll per Bag